## PRODUCT SPECIFICATION

Model NO.	NG150
Nominal Capacity(AH)	150Ah
Nominal Voltage(V)	3.7V
Standard Charge Current(A)	0.5C
Maximum charge current(A)	1C
Impedance( $\Omega$ )	$0.2 m\Omega$
Max. discharge current(A)	2C
Max.charge voltage(V)	3.65V
Discharge cut-off voltage(V)	2.5V
Charge working temp.(°C)	0~55°C
Discharge working temp.(°C)	-20~55°C
Cycle life	4000 Cycles
Brand	EVE/CATL/REPT/NARADA/GOTION/LISHEN



## **PRODUCT FEATURES**



Completely sealed





power

Extended cycle life Extreme light weight



protection

**Broad application** 

VDA compliant

Positive Electrode **Explosion-Proof Valve** Complete QR Code Negative Electrode 75mm 174mm 102mm

## **LONG BATTERY LIFE**





## PRODUCT APPLICATIONS



**Energy Storage Systems** 

Generation-side energy storage I Grid-side energy storage I Power-side energy storage



Pure Electric Private Car I Pure Electric Operating Vehicle



Road passenger vehicles 1 Logistics Delivery Vehicle 1 Heavy Duty Transport Vehicle Road cleaning vehicles | Construction Machinery Vehicle | Two-wheeled vehicles Ships I Special application vehicles

