



Product Specification

Model No.	NSPX-600W	NSPX-1200W
Battery Capacity	600Wh/162240mAh	1200mAh/324480mAh
Charging Time	≈ 3.5h (Combination Charging) Simultaneous Charge-and-Discharge Function	
Battery Cell Type	lithium ion Battery	
Charging Temperature	-15~40°C	
Discharging Temperature	-20~60°C	
Overload Protection	Protection Method: 1200W/1S	Protection Method: 2400W/1S
Ac Interface Standard Shape	US/Jp/Australia/European/Uk PLUG	
Ac Output Waveform Type	Pure Sine Wave	
Ac Rated Output Voltage	US/Jp: 100V-120V CN/EU/AU/UK: 220V-240V	
Default Frequency	US/Jp: 60Hz CN/EU/AU/UK: 50Hz	
Cigarette Lighter Interface	12V/10A	
Solar Input Interface	Charging Voltage Range: 12V~30V	
Usb Interface	USB-A1*2: 5V/2.4A USB-A2(QC3.0): 5V/3A, 9V2A, 12V1.5A	
Usb-c Interface	PD Interface Bi-directional Charging and Discharging	
Led Light Modes	1, Always On 2, Medium Brightness 3, Blink Mode 4, SOS Mode	
Combination Charging	DC100W+PD65W	
Selling Point	Accurate power control/Cost effective	
Future Upgrade	Series Products/Bi-directional fast charging (bi-directional inverter)	
Dimensions	306×171×202mm	413×203×232mm

Packing List



Power station



USB cable



User manual



Adapter

Product Overview

Thank you very much for using our portable power station product. In the design of this product, a multi-level safety mechanism is adopted, and the product safety and reliability are fully guaranteed. It has multi-port AC output and DC output functions, which can meet the power supply needs of mobile phones, notebook computers, cameras, TV sets, various chargers, game consoles, DVD players, small electrical tools and other equipments, and built-in LED lighting.



Warranty

1 year



Approx. Weight

600W:
11lbs (5kgs)

1200W:
20lbs (9kgs)