PRODUCT SPECIFICATION

Model NO.	NG310
Nominal Capacity(AH)	310Ah
Nominal Voltage(V)	3.2V
Standard Charge Current(A)	0.5C
Maximum charge current(A)	1C
$Impedance(\Omega)$	$0.2 m \Omega$
Max. discharge current(A)	2C
Max.charge voltage(V)	3.65V
Discharge cut-off voltage(V)	2.5V
Charge working temp.(°C)	0~55°C
Discharge working temp.(°C)	-20~55°C
Cycle life	6000 Cycles
Brand	BYD



PRODUCT FEATURES



Completely sealed

Extreme light weight





Superior cranking





protection



Broad application



VDA compliant

Positive Electrode Complete QR Code Explosion-Proof Valve Negative Electrode 71mm . 207mm 173mm

LONG BATTERY LIFE





PRODUCT APPLICATIONS



Energy Storage Systems

Generation-side energy storage | Grid-side energy storage | Power-side energy storage



Pure Electric Private Car | Pure Electric Operating Vehicle



Business Applications

Road passenger vehicles | Logistics Delivery Vehicle | Heavy Duty Transport Vehicle Road cleaning vehicles | Construction Machinery Vehicle | Two-wheeled vehicles Ships I Special application vehicles

